

**Technical specifications**  
**GRABOPROTECT RAIN**  
**Covering**

**1. Technical specifications**

**Issued by:** Graboplast Floor Covering Manufacturers Ltd.  
H-9023 Győr Fehérvári út 16/b

**Purpose:** technical requirements defining the quality of wall coverings in rolls


**2. Main characteristics**

**Designations:** covering

**Film:** PVC

**Substrate:** glass fibre mat

**3. Technical Data of the Product**

Parameter	Specification	Tolerance	Test method
Thickness mm	<b>0,7</b>	+/-0,1	ISO 2286
Linear change in dimensions % - length	<b>+/-0,2</b>	max.	MSZ EN 434
Linear change in dimensions % - cross	<b>+/-0,2</b>	max.	MSZ EN 434
Washability	<b>highly wash resistant</b>		≈
Colour-fastness to light	<b>5</b>	min.	ISO 105 B02 3
Chemical resistance - 50% ethyl alcohol contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Chemical resistance - 5% fatty alcohol sulphonate contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Chemical resistance - 5% acetic acid contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Chemical resistance - petrol contact time 120 min	<b>no change</b>	appr.	MSZ EN 423
Weight g/m <sup>2</sup>	<b>650</b>	appr.	ISO 2286
Weight of substrate g/m <sup>2</sup>	<b>27</b>	appr.	ISO 3801
Width of rolls m	<b>1,40</b>		
Hanging	<b>adhesive should be applied to the wall covering, and also to the wall after being diluted</b>		

**Valid from:**

03.03.2009.

**Approved by:**

Reményi István  
Leader of Quality Assurance