



## MaxxPlay

### Cleaning and Maintenance Information for MaxxPlay Poured Polyurethane Flooring System

In order to prevent future dirt build-up and marks on the floor, be sure to follow these guidelines to help maintain the great appearance of your MaxxPlay floor. Your cleaning schedule will depend on how often the floor is used and its activities.

1. Daily; use a dust mop on your floor to remove any excess dirt, dust and debris. Do NOT use a mop head that requires any treatment as they will often leave a film residue. (A recommended product, if needed, is SOLSAN Dust Mop Treatment, manufactured by Johnson-Diversey.)
2. Wet mop any spills and remove large amounts of dirt as soon as possible
3. Your MaxxPlay floor should be wet-mopped as needed. Use a neutral floor cleaner (PH of 7.0-7.5) with warm water. A recommended product is PROFIL Oil & Grease Remover manufactured by Johnson-Diversey.
4. Deep cleaning your MaxxPlay floor should be performed monthly depending on use. A walk behind automatic scrubber (or ride-on for larger areas) works well. It is important to use the double-scrub method, allowing the cleaning solution to stay on the floor for at least 10 minutes before scrubbing and vacuuming. Red or green scrubbing pads are recommended. Alternatively, a standard floor buffer works extremely well. Use two mop buckets; one with the cleaning solution and warm water, the other with clean cold water. Apply cleaning solution and allow to stand 5-10 minutes before scrubbing. Rinse with clean water; change water frequently.
5. Do NOT allow the use of abrasive brushes or pads (brown, black, high productivity), steel wool, or non-recommended solvents on your MaxxPlay floor. Also do not use any high speed buffers (1100 rpm or higher).
6. Do NOT use wax of any kind. Check all cleaning agents or treatments for wax that you will be using on your floor.



## MaxxPlay

### SPOT REMOVAL

Remove difficult stains and/or scuff marks with a non-abrasive cleaner. Stronger cleaning agents (e.g., acetone, denatured alcohol or xylene-dampened cloth) can be used for tar removal. Floor must be rinsed with water following use of solvent. FAILURE TO REMOVE SOLVENT COULD RESULT IN PERMANENT DISCOLORATION OF FLOOR. Before using any solvents, test a small area (in corner, behind bleachers, for example) to determine best results.

### IMPORTANT!

Keep dust and grit off floor. (Use floor mats at entrances to gym and high-traffic areas).

- AVOID use of low-quality footwear (e.g., black-soled shoes) that cause excessive scuffing.
- Tables, chairs and moveable equipment should have proper functioning "glides" to minimize indentations.
- Do NOT allow water or liquids to stand on floor.
- Avoid phosphates, solvents and all moderate-to-high sudsing products.
- When using any Johnsen-Diversey product, please contact the manufacturer directly for complete information at 800-827-5427 x130. A local representative should be glad to assist with a demonstration and explanation of product uses and applications.

Call Traction's technical department should you have any questions or concerns:

866-757-5569

[www.nasfrtraction.com](http://www.nasfrtraction.com)