

## graboflex GYMFIT 25




Property	Standard	Unit	Result
----------	----------	------	--------

DESCRIPTION			
Surface	-	-	PUR Surface
Backing	-	-	Closed cell PVC foam
Thickness	EN 428	mm	2,5
Weight	EN 430	kg/m <sup>2</sup>	2
Width	EN 426	m	2
Standard roll length	EN 426	m	25 ± 10%
Maximal roll length	EN 426	m	30

CLASSIFICATION			
Product specification	EN 651 Vinyl floor covering for indoor sport purposes Meets the requirement of EN 14904 on a sub-construction		
Thermal resistance	-	m <sup>2</sup> K/W	0,02
Reaction to fire	EN 13501	-	C <sub>fl</sub> -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

SPORT PROPERTIES			
Friction	PrEN 14903	-	0,4-0,6
Ball rebound	EN 12235	%	> 90
Specular gloss	EN 2813	%	< 30

TECHNICAL CHARACTERISTICS			
Dimensional stability	EN 434	%	± 0,2
Indentation resistance	EN 1516	mm	0,19
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN 423	-	no change
Abrasion group	EN 660-1		T

OTHERS		
Limited warranty		7 years
Cleanability		Easy to clean
Environmental attributes		No periodic renewal needed; Solvent and heavy metal free

**GRABOPLAST Floor Covering Manufacturers Ltd.**  
 H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100  
 mail@graboplast.hu www.graboplast.hu