

graboflex START

Property	Standard	Unit	Result
----------	----------	------	--------

DESCRIPTION

Surface	-	-	CLP
Backing	-	-	Closed cell PVC foam
Thickness	EN 428	mm	4
Weight	EN 430	kg/m ²	2,3
Width	EN 426	m	2
Standard roll length	EN 426	m	20 ± 10%
Maximal roll length	EN 426	m	25

CLASSIFICATION

Product specification	EN 651 Vinyl floor covering for indoor sport purposes Meets the requirement of EN 14904 on a sub-floor		
Thermal resistance	-	m ² K/W	0,03
Reaction to fire	EN 13501	-	C _{fl} -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

SPORT PROPERTIES

Ball rebound	EN 12235	%	> 90
Specular gloss	EN 2813	%	< 30

TECHNICAL CHARACTERISTICS

Dimensional stability	EN 434	%	± 0,2
Indentation resistance	EN 433	mm	0,35
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN 423	-	no change
Abrasion group	EN 660-1		T

OTHERS

Limited warranty		5 years
Environmental attributes		No periodic renewal needed; Solvent and heavy metal free

GRABOPLAST Floor Covering Manufacturers Ltd.
 H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100
 mail@graboplast.hu www.graboplast.hu